

5.1.4 Dolby Atmos® Surround – Floor Standing Speaker, Monitor Speaker, On Wall Speaker and On Ceiling Speakers.



FRONT SOUNDFIELD – Pre wire for left and right front in speaker locations (Floor Standing Speaker, Monitor Speaker or On Wall Speaker to Be Determined) and one center speaker location. (Monitor Speaker or On Wall Speaker to Be Determined)

LOW FREQUENCY EFFECTS – Pre wire for one powered subwoofer location. (Floor Standing to Be Determined)

REAR SOUNDFIELD – Pre wire for one sets of left and right back rear speaker locations. (Floor Standing Speaker, Monitor Speaker or On Wall Speaker to Be Determined)

HEIGHT SPEAKERS - Pre wire for two sets left and right surface mount height speaker locations. (Monitor Speakers and or On Ceiling Speakers to Be Determined)

Pre Wire Materials

(9) 14 Awg (2) Conductor. (Speaker Cable).

(1) Coax RG59. (Low Frequency Effects).

Speaker Equipment

(2) Left and Right Front Speakers.(Floor Standing Speaker, Monitor Speaker or On Wall Speaker to Be Determined)

(1) Center Speakers.(Monitor Speaker or On Wall Speaker to Be Determined)

(1) Subwoofer. (Floor Standing to Be Determined)

(2) Left and Right Back Rear Speaker.(Monitor Speaker or On Wall Speaker to Be Determined)

(4) Left And Right Surface Mount Height Speaker.(Monitor Speaker and or On Ceiling Speaker to Be Determined)